Model Content Export

Table of content:

DIBA: Data Workflow Brands - OFFLINE
DIBA: Data Workflow Brands - ONLINE
BPM: Campaign Management (with BA)

DIBA: Data Workflow Brands - OFFLINE



Instances

Start (Start Event)

Position	STRING	NODE x:2cm y:4.5cm index:1
External tool coupling	STRING	
Time period	ENUMERATION	Per year
Abandon after tolerance waiting time	ENUMERATION	no
Tolerance waiting time	TIME	00:000:00:00:00
Categories	STRING	
Documentation	STRING	
Term	STRING	
Order	INTEGER	0
Description	STRING	
Comment	STRING	
Trigger	STRING	
Result	STRING	
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated cycle time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Info on results	STRING	
Cost driver	STRING	
Cost driver quantity	INTEGER	0
Aggregated personnel costs	DOUBLE	0
Beschreibung	STRING	
Kommentar	STRING	
Bezeichnung	STRING	Prozeßstart
Open questions	STRING	
Implementing control	ENUMERATION	no
Show name	ENUMERATION	No
Type	ENUMERATION	Top-level
Message	ENUMERATION	No
Timer	ENUMERATION	No
Conditional	ENUMERATION	No
Signal	ENUMERATION	No
Escalation	ENUMERATION	No
Error	ENUMERATION	No
Compensation	ENUMERATION	No
Parallel	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Collection	ENUMERATION	No

Object type	ENUMERATION	Information
Cardinality	STRING	
Details	LONGSTRING	
Timer type	ENUMERATION	Date

GET Articles (Get task)

Position	STRING	NODE x:6cm y:4.5cm w:3.36cm h:1.8cm index:2
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Get type	ENUMERATION	Local file
Google spreadsheet ID	STRING	1DnkN97albrhGbxlClW5kqhXk4DDQ60cBe4WIIERKp_U
Count	STRING	571
R operation log	LONGSTRING	C:\Program Files\R\R-3.2.0\bin>Rscript.exe C:\Users\wutz\AppData\Local\Temp\adoce5f1a99-4f22-462 Attache Paket: 'dplyr' The following objects are masked from 'package:stats': filter, lag The following objects are masked from 'package:base': intersect, setdiff, setequal, union

GET Customers (Get task)

Position	STRING	NODE x:6cm y:12cm w:3.36cm h:1.8cm index:4
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00

Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	https://docs.google.com/spreadsheets/d/1lXTvh4RNaubXIs
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Get type	ENUMERATION	Local file
Google spreadsheet ID	STRING	1lXTvh4RNaubXIsjK6BjRnNC8O2gTd0JxjbexrSvM-SM
Count	STRING	20000
R operation log	LONGSTRING	C:\Program Files\R\R-3.2.0\bin>Rscript.exe C:\Users\wutz\AppData\Local\Temp\adofa91b68b-a859-49 Attache Paket: 'dplyr' The following objects are masked from 'package:stats': filter, lag The following objects are masked from 'package:base': intersect, setdiff, setequal, union

GET Transactions (Get task)

Position	STRING	NODE x:6cm y:8cm w:3.36cm h:1.8cm index:6
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes

Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Get type	ENUMERATION	Local file
Google spreadsheet ID	STRING	1dzWJGdlsv7x77QHCZX0CfdfwI1EiAUaC8Rr7NIwCNEA
Count	STRING	185835
R operation log	LONGSTRING	C:\Program Files\R\R-3.2.0\bin>Rscript.exe C:\Users\wutz\AppData\Local\Temp\ado9a73127d-5e4c-42 Attache Paket: 'dplyr' The following objects are masked from 'package:stats': filter, lag The following objects are masked from 'package:base': intersect, setdiff, setequal, union

GET Twitter Followers (Cache) (Get task)

Position	STRING	NODE x:6cm y:15.5cm w:3.36cm h:1.8cm index:8
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0

Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Get type	ENUMERATION	Local file
Google spreadsheet ID	STRING	
Count	STRING	1002
R operation log	LONGSTRING	C:\Program Files\R\R-3.2.0\bin>Rscript.exe C:\Users\wutz\AppData\Local\Temp\ado53f7daec-0132-49 Attache Paket: 'dplyr' The following objects are masked from 'package:stats': filter, lag The following objects are masked from 'package:base': intersect, setdiff, setequal, union

MERGE: Article and Transaction by ArticleNr (Merge task)

Position	STRING	NODE x:11.5cm y:4.5cm w:3.36cm h:1.8cm index:10
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0

Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Output (CSV)	STRING	
Merge type	ENUMERATION	Left (outer) join
Merge by	STRING	ArticleNr
Count	STRING	185835
R operation log	LONGSTRING	C:\Program Files\R\R-3.2.0\bin>Rscript.exe C:\Users\wutz\AppData\Local\Temp\ado38c599dd-d0c3-49 Attache Paket: 'dplyr' The following objects are masked from 'package:stats': filter, lag The following objects are masked from 'package:base': intersect, setdiff, setequal, union

GROUP: by Brand~Customer (Group task)

Position	STRING	NODE x:17cm y:4.5cm w:3.36cm h:1.8cm index:13
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified

Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Logical operator	ENUMERATION	all
Group expression	STRING	Brand~CustomerNr
Count	STRING	19996
R operation log	LONGSTRING	C:\Program Files\R\R-3.2.0\bin>Rscript.exe C:\Users\wutz\AppData\Local\Temp\ado6f715bca-24fd-434 Attache Paket: 'dplyr' The following objects are masked from 'package:stats': filter, lag The following objects are masked from 'package:base': intersect, setdiff, setequal, union

SUBSET: NOT Adidas Customer (Subset task)

Position	STRING	NODE x:22cm y:4.5cm w:3.36cm h:1.8cm index:15
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information

Completion condition	STRING	
Loop condition (standard)	STRING	
Logical operator	ENUMERATION	all
Subset expression	STRING	[-grep("\\Adidas+", %INPUT%$Brand),]
Count	STRING	1267
R operation log	LONGSTRING	C:\Program Files\R\R-3.2.0\bin>Rscript.exe C:\Users\wutz\AppData\Local\Temp\ado99d7e1c9-52bf-4fa Attache Paket: 'dplyr' The following objects are masked from 'package:stats': filter, lag The following objects are masked from 'package:base': intersect, setdiff, setequal, union

MERGE: Not Adidas Customer with Customer by CustomerNr (Merge task)

Position	STRING	NODE x:28cm y:4.5cm w:3.36cm h:1.8cm index:17
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Output (CSV)	STRING	
Merge type	ENUMERATION	Left (outer) join
Merge by	STRING	CustomerNr
Count	STRING	1267
R operation log	LONGSTRING	C:\Program Files\R\R-3.2.0\bin>Rscript.exe C:\Users\wutz\AppData\Local\Temp\ado8b0d5b70-98ac-4c Attache Paket: 'dplyr' The following objects are masked from 'package:stats': filter, lag The

		following objects are masked from 'package:base': intersect, setdiff, setequal, union

FUZZY JOIN: TwitterFollower and Not Adidas Customer (by nickname and fullname) (Fuzzy join)

Position	STRING	NODE x:39cm y:4.5cm w:3.36cm h:1.8cm index:20
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Output (CSV)	STRING	
Merge type	ENUMERATION	Natural (inner) join
Merge by	STRING	
Fuzzy columns	STRING	"fullname", "nickname"
Count	STRING	1267
R operation log	LONGSTRING	C:\Program Files\R\R-3.2.0\bin>Rscript.exe C:\Users\wutz\AppData\Local\Temp\adoa4d4d04e-a54b-41 Attache Paket: 'dplyr' The following objects are masked from 'package:stats': filter, lag The following objects are masked from 'package:base': intersect, setdiff, setequal, union 1 rows of x are exactly matched on all variables Warning messages: 1: In inner_join_impl(x, y, byx, byy) : joining character vector and factor, coercing into character vector 2: In inner_join_impl(x, y, byx, byy) : joining factors with different levels, coercing to character vector 3: In anti_join_impl(x,

		y, byx, byy) : joining character vector and factor, coercing into character vector 4: In anti_join_impl(x, y, byx, byy) : joining factors with different levels, coercing to character vector

SELECT: Customer Not Adidas/Follower (distance < 0.2) (Select task)

Position	STRING	NODE x:44cm y:4.5cm w:3.36cm h:1.8cm index:23
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Logical operator	ENUMERATION	all
Count	STRING	5
R operation log	LONGSTRING	C:\Program Files\R\R-3.2.0\bin>Rscript.exe C:\Users\wutz\AppData\Local\Temp\ado50e6605b-8246-4c Attache Paket: 'dplyr' The following objects are masked from 'package:stats': filter, lag The following objects are masked from 'package:base': intersect, setdiff, setequal, union 1 rows of x are exactly matched on all variables Warning messages: 1: In inner_join_impl(x, y, byx, byy) : joining character vector and factor, coercing into character vector 2: In inner_join_impl(x, y, byx, byy) : joining factors with different levels, coercing to character vector 3: In anti_join_impl(x, y, byx, byy) : joining character vector and factor,

		coercing into character vector 4: In anti_join_impl(x, y, byx, byy) : joining factors with different levels, coercing to character vector

End (End Event)

Position	STRING	NODE x:48.5cm y:4.5cm index:25
External tool coupling	STRING	
Type	ENUMERATION	local
Categories	STRING	
Documentation	STRING	
Representation	ENUMERATION	without name
Order	INTEGER	0
Description	STRING	
Comment	STRING	
Bezeichnung	STRING	Ende
Beschreibung	STRING	
Kommentar	STRING	
Show name	ENUMERATION	No
Open questions	STRING	
Message	ENUMERATION	No
Signal	ENUMERATION	No
Escalation	ENUMERATION	No
Error	ENUMERATION	No
Compensation	ENUMERATION	No
Terminate	ENUMERATION	No
Cancel	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Cardinality	STRING	
Details	LONGSTRING	

COMBINE fullname (first_name + last_name) (Combine task)

Position	STRING	NODE x:32.5cm y:4.5cm w:3.36cm h:1.8cm index:27
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below

Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Logical operator	ENUMERATION	all
Group expression	STRING	
Left column	STRING	first_name
Right column	STRING	last_name
New column	STRING	fullname
Count	STRING	1267
R operation log	LONGSTRING	C:\Program Files\R\R-3.2.0\bin>Rscript.exe C:\Users\wutz\AppData\Local\Temp\adoe9bf54b2-edce-42 Attache Paket: 'dplyr' The following objects are masked from 'package:stats': filter, lag The following objects are masked from 'package:base': intersect, setdiff, setequal, union

Plot-59611 (Plot)

Position	STRING	NODE x:39cm y:11cm w:11.5cm h:11.5cm index:29
External tool coupling	STRING	
Categories	STRING	
Documentation	STRING	
Text	STRING	
Font size	ENUMERATION	10
Font style	ENUMERATION	Standard
Notiz	STRING	
Calculate size of graphic automatically	ENUMERATION	Yes
__NameGeneration__	STRING	NAMEGEN srcattr:"__hatNotiz__"
Color	STRING	lemonchiffon
Show description of the attachments	ENUMERATION	No
Title	STRING	
Show title	ENUMERATION	No
Plot type	ENUMERATION	Histogram
Data	ENUMERATION	Data
Column	STRING	distance

Plot-59800 (Plot)

Position	STRING	NODE x:26cm y:17.5cm w:11cm h:11cm index:31
External tool coupling	STRING	
Categories	STRING	
Documentation	STRING	
Text	STRING	
Font size	ENUMERATION	10
Font style	ENUMERATION	Standard
Notiz	STRING	
Calculate size of graphic automatically	ENUMERATION	Yes
__NameGeneration__	STRING	NAMEGEN srcattr:"__hatNotiz__"
Color	STRING	lemonchiffon
Show description of the attachments	ENUMERATION	No
Title	STRING	
Show title	ENUMERATION	No
Plot type	ENUMERATION	Bar chart
Data	ENUMERATION	Metadata
Column	STRING	CompletePercentage

Relations

Start->GET Articles(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:3
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process

		diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	1
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	

Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Start->GET Customers(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 1 x1:2cm y1:12cm index:5
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm

		w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	2
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Start->GET Transactions(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 1 x1:2cm y1:8cm index:7
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition

		probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	3
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Start->GET Twitter Followers (Cache)(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 1 x1:2cm y1:15.5cm index:9
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL

		fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	4
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR

"Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

GET Articles->MERGE: Article and Transaction by ArticleNr(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 1 x1:8cm y1:4.5cm index:11 MIDDLE x:8.33cm y:4.5cm
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It

		can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	5
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	X
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

GET Transactions->MERGE: Article and Transaction by ArticleNr(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 2 x1:9cm y1:8cm x2:9cm y2:5cm index:12 MIDDLE x:8.42cm y:8cm
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") {

		FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	6
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	Y
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

MERGE: Article and Transaction by ArticleNr->GROUP: by Brand~Customer(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:14
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4

		x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	0
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id"

		CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

GROUP: by Brand~Customer->SUBSET: NOT Adidas Customer(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:16
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The

		'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	8
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

SUBSET: NOT Adidas Customer->MERGE: Not Adidas Customer with Customer by CustomerNr(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:18 MIDDLE x:24.43cm y:4.5cm
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT

		color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	0
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	X
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

GET Customers->MERGE: Not Adidas Customer with Customer by CustomerNr(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 2 x1:25cm y1:12cm x2:25cm y2:5cm index:19 MIDDLE x:8.4cm y:12cm
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process

		diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	0
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	Y
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

GET Twitter Followers (Cache)->FUZZY JOIN: TwitterFollower and Not Adidas Customer (by nickname and fullname)(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 2 x1:35cm y1:15.5cm x2:35cm y2:5cm index:21 MIDDLE x:8.52cm y:15.5cm
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition

		condition when it follows a Decision or Parallelity.
Connector number	INTEGER	11
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	Y
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

COMBINE fullname (first_name + last_name)->FUZZY JOIN: TwitterFollower and Not Adidas Customer (by nickname and fullname)(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:22 MIDDLE x:34.7cm y:4.5cm
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d =

		"above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	12
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	X
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

FUZZY JOIN: TwitterFollower and Not Adidas Customer (by nickname and fullname)->SELECT: Customer Not Adidas/Follower (distance < 0.2)(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:24
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType =

		"Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	13
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

SELECT: Customer Not Adidas/Follower (distance < 0.2)->End(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:26
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	14

Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

MERGE: Not Adidas Customer with Customer by CustomerNr->COMBINE fullname (first_name + last_name)(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:28
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm

		w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	0
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

FUZZY JOIN: TwitterFollower and Not Adidas Customer (by nickname and fullname)->Plot-59611(feeds)

Positions	STRING	EDGE 0 index:30
GraphRep	STRING	
AttrRep	STRING	

FUZZY JOIN: TwitterFollower and Not Adidas Customer (by nickname and fullname)->Plot-59800(feeds)

Positions	STRING	EDGE 1 x1:38cm y1:18.5cm index:32
GraphRep	STRING	
AttrRep	STRING	

DIBA: Data Workflow Brands - ONLINE



Edit the model attributes to display your copyright info
Powered by ADOxx
www.adoxx.org

Instances

Start Event-52803 (Start Event)

Position	STRING	NODE x:2cm y:4.5cm index:1
External tool coupling	STRING	
Time period	ENUMERATION	Per year
Abandon after tolerance waiting time	ENUMERATION	no
Tolerance waiting time	TIME	00:000:00:00:00
Categories	STRING	
Documentation	STRING	
Term	STRING	
Order	INTEGER	0
Description	STRING	
Comment	STRING	
Trigger	STRING	
Result	STRING	
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated cycle time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Info on results	STRING	
Cost driver	STRING	
Cost driver quantity	INTEGER	0
Aggregated personnel costs	DOUBLE	0
Beschreibung	STRING	
Kommentar	STRING	
Bezeichnung	STRING	Prozeßstart
Open questions	STRING	
Implementing control	ENUMERATION	no
Show name	ENUMERATION	No
Type	ENUMERATION	Top-level
Message	ENUMERATION	No
Timer	ENUMERATION	No
Conditional	ENUMERATION	No
Signal	ENUMERATION	No
Escalation	ENUMERATION	No
Error	ENUMERATION	No
Compensation	ENUMERATION	No
Parallel	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Cardinality	STRING	
Details	LONGSTRING	

Timer type	ENUMERATION	Date

GET Articles (Get task)

Position	STRING	NODE x:6cm y:4.5cm w:3.36cm h:1.8cm index:2
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	https://docs.google.com/spreadsheets/d/1DnkN97albrhGb
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Get type	ENUMERATION	Google spreadsheet (CSV)
Google spreadsheet ID	STRING	1DnkN97albrhGbxlClW5kqhXk4DDQ60cBe4WIIERKp_U
Count	STRING	571
R operation log	LONGSTRING	

GET Customers (Get task)

Position	STRING	NODE x:6cm y:12cm w:3.36cm h:1.8cm index:4
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1

Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	https://docs.google.com/spreadsheets/d/1lXTvh4RNaubXIs
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Get type	ENUMERATION	Google spreadsheet (CSV)
Google spreadsheet ID	STRING	1lXTvh4RNaubXIsjK6BjRnNC8O2gTd0JxjbexrSvM-SM
Count	STRING	20000
R operation log	LONGSTRING	

GET Transactions (Get task)

Position	STRING	NODE x:6cm y:8cm w:3.36cm h:1.8cm index:6
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00

Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Get type	ENUMERATION	URL (CSV)
Google spreadsheet ID	STRING	1dzWJGdlsv7x77QHCZX0CfdfwI1EiAUaC8Rr7NIwCNEA
Count	STRING	185835
R operation log	LONGSTRING	

GET Twitter Followers (Cache) (Get task)

Position	STRING	NODE x:6cm y:15.5cm w:3.36cm h:1.8cm index:8
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	https://docs.google.com/spreadsheets/d/1JeTKvGZ2jur0Xe
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below

Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Get type	ENUMERATION	Google spreadsheet (CSV)
Google spreadsheet ID	STRING	1JeTKvGZ2jur0Xe8RE91UedohUxiXka4yuyPSLU4CXzg
Count	STRING	1002
R operation log	LONGSTRING	

MERGE: Article and Transaction by ArticleNr (Merge task)

Position	STRING	NODE x:11.5cm y:4.5cm w:3.36cm h:1.8cm index:10
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Output (CSV)	STRING	
Merge type	ENUMERATION	Left (outer) join

Merge by	STRING	ArticleNr
Count	STRING	185835
R operation log	LONGSTRING	

GROUP: by Brand~Customer (Group task)

Position	STRING	NODE x:17cm y:4.5cm w:3.36cm h:1.8cm index:13
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Logical operator	ENUMERATION	all
Group expression	STRING	Brand~CustomerNr
Count	STRING	19996
R operation log	LONGSTRING	

SUBSET: NOT Adidas Customer (Subset task)

Position	STRING	NODE x:22cm y:4.5cm w:3.36cm h:1.8cm index:15
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no

Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Logical operator	ENUMERATION	all
Subset expression	STRING	[-grep("\\Adidas+", %INPUT%$Brand),]
Count	STRING	1267
R operation log	LONGSTRING	

MERGE: Not Adidas Customer with Customer by CustomerNr (Merge task)

Position	STRING	NODE x:28cm y:4.5cm w:3.36cm h:1.8cm index:17
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	

Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Output (CSV)	STRING	
Merge type	ENUMERATION	Left (outer) join
Merge by	STRING	CustomerNr
Count	STRING	
R operation log	LONGSTRING	

FUZZY JOIN: TwitterFollower and Not Adidas Customer (by nickname and fullname) (Fuzzy join)

Position	STRING	NODE x:38.5cm y:4.5cm w:3.36cm h:1.8cm index:20
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0

Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Output (CSV)	STRING	
Merge type	ENUMERATION	Natural (inner) join
Merge by	STRING	
Fuzzy columns	STRING	"fullname", "nickname"
Count	STRING	
R operation log	LONGSTRING	

SELECT: Customer Not Adidas/Follower (distance < 0.2) (Select task)

Position	STRING	NODE x:43.5cm y:4.5cm w:3.36cm h:1.8cm index:23
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified

Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Logical operator	ENUMERATION	all
Count	STRING	1267
R operation log	LONGSTRING	

End Event-55012 (End Event)

Position	STRING	NODE x:48cm y:4.5cm index:25
External tool coupling	STRING	
Type	ENUMERATION	local
Categories	STRING	
Documentation	STRING	
Representation	ENUMERATION	without name
Order	INTEGER	0
Description	STRING	
Comment	STRING	
Bezeichnung	STRING	Ende
Beschreibung	STRING	
Kommentar	STRING	
Show name	ENUMERATION	No
Open questions	STRING	
Message	ENUMERATION	No
Signal	ENUMERATION	No
Escalation	ENUMERATION	No
Error	ENUMERATION	No
Compensation	ENUMERATION	No
Terminate	ENUMERATION	No
Cancel	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Cardinality	STRING	
Details	LONGSTRING	

COMBINE fullname (first_name + last_name) (Combine task)

Position	STRING	NODE x:33cm y:4.5cm w:3.36cm h:1.8cm index:27
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0

Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Logical operator	ENUMERATION	all
Group expression	STRING	
Left column	STRING	first_name
Right column	STRING	last_name
New column	STRING	fullname
Count	STRING	
R operation log	LONGSTRING	

Get Twitter Followers @ADIDAS (Get Twitter Followers)

Position	STRING	NODE x:6cm y:19.5cm w:3.36cm h:1.8cm index:29
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	below
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No

Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	
Get type	ENUMERATION	Local file
Google spreadsheet ID	STRING	
Count	STRING	
Consumer key	STRING	F0rGTmiZokOQd0DlcsF68Q
Consumer secret	STRING	5GuD0Cl6KfCMXYFB0YNTTOO6ErtGNAsVVn0J2Q1zAs
Access token	STRING	195495416-Mi08ZdI4vce04HVV4CXwmqh2SyFEXlsHdSub
Access secret	STRING	EkPXLsHMsr2mK5DBmZ10qlbkYdViwmaNq8J9l0SkaqEY
Twitter handle	STRING	@adidas
R operation log	LONGSTRING	

Relations

Start Event-52803->GET Articles(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:3
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF

		(s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	1
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Start Event-52803->GET Customers(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 1 x1:2cm y1:12cm index:5
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition

		condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	2
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Start Event-52803->GET Transactions(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 1 x1:2cm y1:8cm index:7
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	

GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	3
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No

Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Start Event-52803->GET Twitter Followers (Cache)(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 1 x1:2cm y1:15.5cm index:9
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") {

		TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	4
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

GET Articles->MERGE: Article and Transaction by ArticleNr(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 1 x1:8cm y1:4.5cm index:11 MIDDLE x:8.33cm y:4.5cm
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v =

		"Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	5
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	X
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

GET Transactions->MERGE: Article and Transaction by ArticleNr(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 2 x1:9cm y1:8cm x2:9cm y2:5cm index:12 MIDDLE x:8.42cm y:8cm
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process

		diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	6
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	Y
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	

Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

MERGE: Article and Transaction by ArticleNr->GROUP: by Brand~Customer(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:14
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm

		w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	0
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

GROUP: by Brand~Customer->SUBSET: NOT Adidas Customer(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:16
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition

		probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	8
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

SUBSET: NOT Adidas Customer->MERGE: Not Adidas Customer with Customer by CustomerNr(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:18 MIDDLE x:24.43cm y:4.5cm
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL

		condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	0
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	X
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR

"Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

GET Customers->MERGE: Not Adidas Customer with Customer by CustomerNr(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 2 x1:25cm y1:12cm x2:25cm y2:5cm index:19 MIDDLE x:8.4cm y:12cm
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of

		activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	10
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	Y
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

GET Twitter Followers (Cache)->FUZZY JOIN: TwitterFollower and Not Adidas Customer (by nickname and fullname)(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 2 x1:36cm y1:15.5cm x2:36cm y2:5cm index:21 MIDDLE x:8.52cm y:15.5cm
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name)

		SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	11
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	Y
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

COMBINE fullname (first_name + last_name)->FUZZY JOIN: TwitterFollower and Not Adidas Customer (by nickname and fullname)(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:22 MIDDLE x:35.4cm y:4.5cm
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL

		fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	12
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	X
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR

"Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

FUZZY JOIN: TwitterFollower and Not Adidas Customer (by nickname and fullname)->SELECT: Customer Not Adidas/Follower (distance < 0.2)(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:24
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It

		can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	13
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

SELECT: Customer Not Adidas/Follower (distance < 0.2)->End Event-55012(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:26
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE {

		FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	14
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

MERGE: Not Adidas Customer with Customer by CustomerNr->COMBINE fullname (first_name + last_name)(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:28
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4

		x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	0
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id"

CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Start Event-52803->Get Twitter Followers @ADIDAS(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 1 x1:2cm y1:19.5cm index:30
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The

		'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	0
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

BPM: Campaign Management (with BA)



Instances

Campaign Management Life Insurance (Start Event)

Position	STRING	NODE x:5cm y:3.5cm index:1
External tool coupling	STRING	
Time period	ENUMERATION	Per year
Abandon after tolerance waiting time	ENUMERATION	no
Tolerance waiting time	TIME	00:000:00:00:00
Categories	STRING	
Documentation	STRING	
Term	STRING	
Order	INTEGER	0
Description	STRING	
Comment	STRING	
Trigger	STRING	
Result	STRING	
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated cycle time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Info on results	STRING	
Cost driver	STRING	
Cost driver quantity	INTEGER	0
Aggregated personnel costs	DOUBLE	0
Beschreibung	STRING	
Kommentar	STRING	
Bezeichnung	STRING	Prozeßstart
Open questions	STRING	
Implementing control	ENUMERATION	no
Show name	ENUMERATION	Yes
Type	ENUMERATION	Top-level
Message	ENUMERATION	No
Timer	ENUMERATION	No
Conditional	ENUMERATION	No
Signal	ENUMERATION	No
Escalation	ENUMERATION	No
Error	ENUMERATION	No
Compensation	ENUMERATION	No
Parallel	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Cardinality	STRING	
Details	LONGSTRING	
Timer type	ENUMERATION	Date

Review campaign readiness (Task)

Position	STRING	NODE x:9cm y:3.5cm w:3.36cm h:1.8cm index:2
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron

Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	center
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	

Select campaign type to launch (Task)

Position	STRING	NODE x:14cm y:3.5cm w:3.36cm h:1.8cm index:3
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0

Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	center
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	

Develop campaign project plan (Task)

Position	STRING	NODE x:52cm y:3.5cm w:3.36cm h:1.8cm index:7
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	center
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No

Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	

Feasible to run campaign according to KPI information? (Exclusive Gateway)

Position	STRING	NODE x:45cm y:3.5cm index:8
External tool coupling	STRING	
Variable type	ENUMERATION	enumeration
Variable scope	ENUMERATION	global
Variable name	STRING	
Variable value	STRING	
Categories	STRING	
Documentation	STRING	
Term	STRING	
Order	INTEGER	0
Description	STRING	
Comment	STRING	
Bezeichnung	STRING	Entscheidung
Kommentar	STRING	
Beschreibung	STRING	
Open questions	STRING	
Type	ENUMERATION	Data-based (without marker)
Show name	ENUMERATION	below
Constraints	ENUMERATION	Unspecified
Cardinality	STRING	

Campaign stopped (End Event)

Position	STRING	NODE x:45cm y:10.5cm index:10
External tool coupling	STRING	
Type	ENUMERATION	local
Categories	STRING	
Documentation	STRING	
Representation	ENUMERATION	without name
Order	INTEGER	0
Description	STRING	
Comment	STRING	
Bezeichnung	STRING	Ende
Beschreibung	STRING	
Kommentar	STRING	
Show name	ENUMERATION	Yes
Open questions	STRING	
Message	ENUMERATION	No
Signal	ENUMERATION	No
Escalation	ENUMERATION	No
Error	ENUMERATION	No
Compensation	ENUMERATION	No
Terminate	ENUMERATION	No
Cancel	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Cardinality	STRING	
Details	LONGSTRING	

End Event-41907 (End Event)

Position	STRING	NODE x:67.5cm y:3.5cm index:12
External tool coupling	STRING	
Type	ENUMERATION	local
Categories	STRING	
Documentation	STRING	
Representation	ENUMERATION	without name
Order	INTEGER	0
Description	STRING	
Comment	STRING	
Bezeichnung	STRING	Ende
Beschreibung	STRING	
Kommentar	STRING	
Show name	ENUMERATION	No
Open questions	STRING	
Message	ENUMERATION	No
Signal	ENUMERATION	No
Escalation	ENUMERATION	No
Error	ENUMERATION	No
Compensation	ENUMERATION	No
Terminate	ENUMERATION	No
Cancel	ENUMERATION	No

Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Cardinality	STRING	
Details	LONGSTRING	

Execute campaign (Sub-Process)

Position	STRING	NODE x:57.5cm y:3.5cm w:3.36cm h:1.8cm index:14
External tool coupling	STRING	
Categories	STRING	
Documentation	STRING	
Term	STRING	
Order	INTEGER	0
Description	STRING	
Comment	STRING	
Bezeichnung	STRING	Prozeßaufruf
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Classification	ENUMERATIONLIST	
__NameGeneration__	STRING	NAMEGEN srcattr:"Referenced subprocess" format:"%m"
Type	ENUMERATION	Embedded
Global	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Loop condition (standard)	STRING	
Completion condition	STRING	
Completion condition (ad-hoc)	STRING	
Suppress Sub-Process	ENUMERATION	No

Campaign Audit (Sub-Process)

Position	STRING	NODE x:63cm y:3.5cm w:3.36cm h:1.8cm index:16
External tool coupling	STRING	
Categories	STRING	
Documentation	STRING	
Term	STRING	
Order	INTEGER	0
Description	STRING	
Comment	STRING	
Bezeichnung	STRING	Prozeßaufruf
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Classification	ENUMERATIONLIST	
__NameGeneration__	STRING	NAMEGEN srcattr:"Referenced subprocess" format:"%m"
Type	ENUMERATION	Embedded
Global	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Loop condition (standard)	STRING	
Completion condition	STRING	
Completion condition (ad-hoc)	STRING	
Suppress Sub-Process	ENUMERATION	No

Business Understanding (Group)

Position	STRING	NODE x:7cm y:1cm w:9.5cm h:11.5cm index:18
External tool coupling	STRING	
Categories	STRING	
Documentation	STRING	
Description	STRING	
Comment	STRING	
Open questions	STRING	
Show name	ENUMERATION	inside

Cardinality	STRING	

Execution (Group)

Position	STRING	NODE x:50cm y:1cm w:10cm h:11.5cm index:19
External tool coupling	STRING	
Categories	STRING	
Documentation	STRING	
Description	STRING	
Comment	STRING	
Open questions	STRING	
Show name	ENUMERATION	inside
Cardinality	STRING	

Monitoring (Group)

Position	STRING	NODE x:60.5cm y:1cm w:5cm h:11.5cm index:20
External tool coupling	STRING	
Categories	STRING	
Documentation	STRING	
Description	STRING	
Comment	STRING	
Open questions	STRING	
Show name	ENUMERATION	inside
Cardinality	STRING	

Business and Data Understanding (Group)

Position	STRING	NODE x:17.5cm y:1cm w:30.5cm h:11.5cm index:21
External tool coupling	STRING	
Categories	STRING	
Documentation	STRING	
Description	STRING	
Comment	STRING	
Open questions	STRING	
Show name	ENUMERATION	inside
Cardinality	STRING	

Analyse inputs (Task)

Position	STRING	NODE x:20.5cm y:3.5cm w:3.36cm h:1.8cm index:22
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	

Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	center
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	

Identify target audience for brand (Task)

Position	STRING	NODE x:25.5cm y:3.5cm w:3.36cm h:1.8cm index:24
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	center
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	

Calculate gross margin (Task)

Position	STRING	NODE x:38.5cm y:3.5cm w:3.36cm h:1.8cm

		index:26
External tool coupling	STRING	
Execution time	TIME	00:000:00:00:00
Waiting time	TIME	00:000:00:00:00
Resting time	TIME	00:000:00:00:00
Transport time	TIME	00:000:00:00:00
Priority	INTEGER	10
Done by	STRING	
Continuous execution	ENUMERATION	no
Max. resource waiting time	TIME	00:000:00:05:00
Cooperative	ENUMERATION	no
Cooperation mode	ENUMERATION	synchron
Average number of participants	INTEGER	1
Min. quota of presence	INTEGER	100
Max. start period	TIME	00:001:00:00:00
Execution interruptable	ENUMERATION	yes
Task stack	ENUMERATION	personal
Categories	STRING	
Documentation	STRING	
Term	STRING	
Status	ENUMERATION	None
Order	INTEGER	0
Costs	DOUBLE	0
Description	STRING	
Comment	STRING	
Info on results	STRING	
Number	DOUBLE	0
Aggregated execution time	TIME	00:000:00:00:00
Aggregated waiting time	TIME	00:000:00:00:00
Aggregated resting time	TIME	00:000:00:00:00
Aggregated transport time	TIME	00:000:00:00:00
Aggregated costs	DOUBLE	0
Aggregated personnel costs	DOUBLE	0
Classification	ENUMERATIONLIST	
EDP transaction costs	DOUBLE	0
EDP batch costs	DOUBLE	0
Printing costs	DOUBLE	0
Postal costs	DOUBLE	0
Bezeichnung	STRING	Aktivität
Beschreibung	STRING	
Kommentar	STRING	
Open questions	STRING	
Type	ENUMERATION	Standard
Display responsible role	ENUMERATION	No
Show name	ENUMERATION	center
Task type	ENUMERATION	Not specified
Global task	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
For compensation	ENUMERATION	No
Loop type	ENUMERATION	Not specified
Sequential execution	ENUMERATION	No
Cardinality	STRING	
Instantiate	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Completion condition	STRING	
Loop condition (standard)	STRING	

Process View (Pool)

Position	STRING	NODE x:0cm y:0cm w:69cm h:13cm index:28
External tool coupling	STRING	
Categories	STRING	
Documentation	STRING	
ParticipantType	ENUMERATION	Role
Role	STRING	
Entity	STRING	
BoundaryVisible	ENUMERATION	Yes
Process Term	STRING	
ProcessType	ENUMERATION	None
Status	ENUMERATION	None
AdHoc	ENUMERATION	No
AdHocOrdering	ENUMERATION	None
AdHocCompletionCondition	STRING	
EnableInstanceCompensation	ENUMERATION	No
Categories (Process)	STRING	
Documentation (Process)	STRING	
SuppressJoinFailure	ENUMERATION	No
Rotate the visualised values by 90 degrees	ENUMERATION	No
Description	STRING	

Comment	STRING	
Open questions	STRING	
Color	STRING	white
Orientation	ENUMERATION	horizontal
Boundary visible	ENUMERATION	Yes
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Process type	ENUMERATION	None
Executable	ENUMERATION	No
Closed	ENUMERATION	No

Target Audience Size (Exclusive Gateway)

Position	STRING	NODE x:29.5cm y:3.5cm index:29
External tool coupling	STRING	
Variable type	ENUMERATION	enumeration
Variable scope	ENUMERATION	global
Variable name	STRING	
Variable value	STRING	
Categories	STRING	
Documentation	STRING	
Term	STRING	
Order	INTEGER	0
Description	STRING	
Comment	STRING	
Bezeichnung	STRING	Entscheidung
Kommentar	STRING	
Beschreibung	STRING	
Open questions	STRING	
Type	ENUMERATION	Data-based (without marker)
Show name	ENUMERATION	below
Constraints	ENUMERATION	Unspecified
Cardinality	STRING	

Campaign stopped due to small audiencce (End Event)

Position	STRING	NODE x:29.5cm y:9.5cm index:31
External tool coupling	STRING	
Type	ENUMERATION	local
Categories	STRING	
Documentation	STRING	
Representation	ENUMERATION	without name
Order	INTEGER	0
Description	STRING	
Comment	STRING	
Bezeichnung	STRING	Ende
Beschreibung	STRING	
Kommentar	STRING	
Show name	ENUMERATION	Yes
Open questions	STRING	
Message	ENUMERATION	No
Signal	ENUMERATION	No
Escalation	ENUMERATION	No
Error	ENUMERATION	No
Compensation	ENUMERATION	No
Terminate	ENUMERATION	No
Cancel	ENUMERATION	No
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Collection	ENUMERATION	No
Object type	ENUMERATION	Information
Cardinality	STRING	
Details	LONGSTRING	

Audience Nike (never bought Nike, interested in Social Networks) (KPI)

Position	STRING	NODE x:37.5cm y:14cm index:33
External tool coupling	STRING	
Categories	STRING	
Documentation	STRING	
Value	STRING	11

Audience ADIDAS (never bought NIKE, interested in Social Networks) (KPI)

Position	STRING	NODE x:37.5cm y:11.5cm index:34
External tool coupling	STRING	
Categories	STRING	
Documentation	STRING	
Value	STRING	5

Potential audience (Aggregation)

Position	STRING	NODE x:31.5cm y:10.5cm w:12cm h:5cm index:35
External tool coupling	STRING	
Categories	STRING	

Documentation	STRING	
Description	STRING	
Comment	STRING	
Color	STRING	lightgray
Representation	ENUMERATION	outside
Lines	ENUMERATION	Normal
Bezeichnung	STRING	Aggregation
Beschreibung	STRING	
Kommentar	STRING	
Font size	ENUMERATION	10
Font style	ENUMERATION	Standard
Display name	ENUMERATION	Yes
Graphical representation	ENUMERATION	Rectangle
Transparent	ENUMERATION	No
Fill	ENUMERATION	Gradient (vertical)
Color (gradient)	STRING	$efefef
Color (border)	STRING	black

Relations

Campaign Management Life Insurance->Review campaign readiness(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:5
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF

		(s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	4
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Campaign Management Life Insurance->Process View(Is inside)

AutoConnect	STRING	

Review campaign readiness->Select campaign type to launch(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:4
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL

		d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	3
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Review campaign readiness->Business Understanding(Is inside)

AutoConnect	STRING	

Review campaign readiness->Process View(Is inside)

AutoConnect	STRING	

Select campaign type to launch->Analyse inputs(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 1 x1:16cm y1:3.5cm index:6
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	7
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black

Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Select campaign type to launch->Business Understanding(Is inside)

AutoConnect	STRING	

Select campaign type to launch->Process View(Is inside)

AutoConnect	STRING	

Develop campaign project plan->Execute campaign(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:13
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT

		color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	10
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Develop campaign project plan->Execution(Is inside)

AutoConnect	STRING	

Develop campaign project plan->Process View(Is inside)

AutoConnect	STRING	

Feasible to run campaign according to KPI information?->Develop campaign project plan(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:9
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL

		fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	7
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	Gross margin > 0
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR

"Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Feasible to run campaign according to KPI information?->Campaign stopped(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 1 x1:45cm y1:6.5cm index:11
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the

		exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	9
Representation	ENUMERATION	left/right
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	Gross margin <= 0
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Feasible to run campaign according to KPI information?->Process View(Is inside)

AutoConnect	STRING	

Feasible to run campaign according to KPI information?->Business and Data Understanding(Is inside)

AutoConnect	STRING	

Campaign stopped->Process View(Is inside)

AutoConnect	STRING	

Campaign stopped->Business and Data Understanding(Is inside)

AutoConnect	STRING	

End Event-41907->Process View(Is inside)

AutoConnect	STRING	

Execute campaign->Campaign Audit(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:15
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL

		d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	8
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Execute campaign->Execution(Is inside)

AutoConnect	STRING

Execute campaign->Process View(Is inside)

AutoConnect	STRING

Campaign Audit->End Event-41907(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:17
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	9
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black

Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Campaign Audit->Monitoring(Is inside)

AutoConnect	STRING	

Campaign Audit->Process View(Is inside)

AutoConnect	STRING	

Business Understanding->Process View(Is inside)

AutoConnect	STRING	

Execution->Process View(Is inside)

AutoConnect	STRING	

Monitoring->Process View(Is inside)

AutoConnect	STRING	

Business and Data Understanding->Process View(Is inside)

AutoConnect	STRING	

Analyse inputs->Identify target audience for brand(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:23
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET

		txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	11
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Analyse inputs->Business and Data Understanding(Is inside)

AutoConnect	STRING	

Analyse inputs->Process View(Is inside)

AutoConnect	STRING	

Identify target audience for brand->Business and Data Understanding(Is inside)

AutoConnect	STRING	

Identify target audience for brand->Process View(Is inside)

AutoConnect	STRING	

Identify target audience for brand->Target Audience Size(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:25
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	12
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black

Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Calculate gross margin->Business and Data Understanding(Is inside)

AutoConnect	STRING	

Calculate gross margin->Process View(Is inside)

AutoConnect	STRING	

Calculate gross margin->Feasible to run campaign according to KPI information?(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 1 x1:43cm y1:3.5cm index:27
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT

		color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	13
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Target Audience Size->Calculate gross margin(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:30
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType =

		"Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	14
Representation	ENUMERATION	above/below
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	Audience Size > 100
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Target Audience Size->Business and Data Understanding(Is inside)

AutoConnect	STRING	

Target Audience Size->Process View(Is inside)

AutoConnect	STRING	

Target Audience Size->Campaign stopped due to small audiencce(Subsequent)

Transition condition	STRING	
Transition probability	STRING	
Visualized values	ENUMERATION	Denomination
Positions	STRING	EDGE 0 index:32
VisibleAttrs	STRING	
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_Subsequent.leo"
Visualization	ENUMERATION	RELATION
Comment	STRING	
GraphRep	STRING	GRAPHREP rounded:0.1cm PEN w:0.05cm EDGE AVAL sModelType: "ModelTypeExp" START IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) { AVAL sStandard: "Default" IF (sStandard = "Yes") { LINE x1:-0.7cm y1:-0.1cm x2:-0.5cm y2:0.1cm } AVAL condExpression: "Transition condition" AVAL fromType: "FromType" IF ((condExpression != "") AND ((fromType = "Task") OR (fromType = "Sub-Process"))) { FILL color:white POLYGON 4 x1:0.0cm y1:0.0cm x2:-0.15cm y2:-0.15cm x3:-0.3cm y3:0.0cm x4:-0.15cm y4:0.15cm } } END IF ((sModelType = "Business process diagram (BPMN 2.0)") OR (sModelType = "Choreography diagram (BPMN 2.0)")) FILL color:black POLYGON 3 x1:-.33cm y1:-.11cm x2:0.0cm y2:0.0cm x3:-.33cm y3:0.11cm ELSE POLYLINE 3 x1:-.3cm y1:.1cm x2:0cm y2:0cm x3:-.3cm y3:-.1cm ENDIF MIDDLE AVAL s:"Rotate the visualised values by 90 degrees" AVAL v:"Visualized values" AVAL d:"Representation" AVAL sp:"Language" AVAL cl:"Font colour" SET maxTxtWidth:(4cm) AVAL name:"Denomination" AVAL transCond:"Transition condition" AVAL transVal:"Transition probability" IF (v = "Denomination") { SET txt1:(name) SET txt2:("") } ELSIF (v = "Transition condition") { SET txt1:(transCond) SET txt2:("") } ELSIF (v = "Transition probability") { SET txt1:("") SET txt2:(transVal) } ELSIF (v = "Transition probability and transition condition") { SET txt1:(transCond) SET txt2:(transVal) } ELSIF (v = "Transition probability and denomination") { SET txt1:(name) SET txt2:(transVal) } ELSE { SET txt1:(name) SET txt2:(transCond) } IF (cl = "black") { IF (s = "Yes") { FONT color:black line-orientation:90 } ELSE { FONT color:black line-orientation:0 } } ELSE { IF (s = "Yes") { FONT color:whitesmoke line-orientation:90 } ELSE { FONT color:whitesmoke line-orientation:0 } } IF (d = "above/below") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:c:(maxTxtWidth) h:b } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:0.2cm w:c:(maxTxtWidth) h:t } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:-0.2cm w:c:(maxTxtWidth) h:b } } } IF (d = "left/right") { IF (s = "Yes") { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.0cm y:-0.2cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:0.0cm y:0.2cm w:r:(maxTxtWidth) h:c } } ELSE { IF (txt1 != "") { TEXT (txt1) line-break:rigorous x:0.2cm y:0.0cm w:l:(maxTxtWidth) h:c } IF (txt2 != "") { TEXT (txt2) line-break:rigorous x:-0.2cm y:0.0cm w:r:(maxTxtWidth) h:c } } }
AnimRep	STRING	
HlpTxt	STRING	The relation 'Subsequent' defines the flow of activities and decisions in a Business Process. It can be used to link all types of objects with the

		exception of 'Variable', 'Random generator', 'Resource', 'Aggregation', 'Performance indicator' and 'Performance indicator overview'. The 'Subsequent' relation may contain a transition condition when it follows a Decision or Parallelity.
Connector number	INTEGER	15
Representation	ENUMERATION	left/right
Font colour	ENUMERATION	black
Kommentar	STRING	
Info zur Übergangsbedingung	STRING	
Bezeichnung	STRING	Nachfolger
Beschreibung	STRING	
Denomination	STRING	Audience Size < 100
Description	LONGSTRING	
__Variants__	LONGSTRING	
Auditing	ENUMERATION	No
Monitoring	ENUMERATION	No
Default	ENUMERATION	No
Immediate	ENUMERATION	No
Category	STRING	
Rotate the visualised values by 90 degrees	ENUMERATION	No
Color	STRING	black
Doku	STRING	NOTEBOOK #---------- LANG "en" #---------- CHAPTER "Description" ATTR "Denomination" ATTR "Description" ATTR "Comment" CHAPTER "Details (BPMN)" ATTR "Auditing" ATTR "Monitoring" ATTR "Default" ATTR "Immediate" ATTR "Category" ATTR "Id" CHAPTER "Details (Simulation)" ATTR "Transition condition" dialog:transcond ATTR "Transition probability"

Campaign stopped due to small audiencce->Business and Data Understanding(Is inside)

AutoConnect	STRING	

Campaign stopped due to small audiencce->Process View(Is inside)

AutoConnect	STRING	

Audience Nike (never bought Nike, interested in Social Networks)->Potential audience(Is inside)

AutoConnect	STRING	

Audience ADIDAS (never bought NIKE, interested in Social Networks)->Business and Data Understanding(Is inside)

AutoConnect	STRING	

Audience ADIDAS (never bought NIKE, interested in Social Networks)->Process View(Is inside)

AutoConnect	STRING	

Audience ADIDAS (never bought NIKE, interested in Social Networks)->Potential audience(Is inside)

AutoConnect	STRING	

Potential audience->Business and Data Understanding(Is inside)

AutoConnect	STRING	

Potential audience->Process View(Is inside)

AutoConnect	STRING	

Potential audience->Target Audience Size(Conversation Link)

Positions	STRING	EDGE 1 x1:34cm y1:6cm index:36
GraphRep	STRING	GRAPHREP start-trans:-0.1cm SHADOW off AVAL sRepr: "Representation" AVAL sRotate: "Rotate the visualised values by 90 degrees" AVAL sName: "Name" PEN w:0.2cm color:$727272 EDGE PEN w:0.05cm color:white EDGE MIDDLE AVAL showName:"Show name" IF (showName = "Yes") IF (sRepr = "above/below") IF (sRotate = "Yes") FONT line-orientation:90 ATTR "Name" text:(sName) line-break:words x:0.2cm y:0.2cm w:c:(2.0cm) h:t ELSE FONT line-orientation:0 ATTR "Name" text:(sName) line-break:words x:0.0cm y:0.2cm w:c:(2.0cm) h:t ENDIF ELSE IF (sRotate = "Yes") FONT line-orientation:90 ATTR "Name" text:(sName) line-break:words x:0.0cm y:-0.2cm w:l:(2.0cm) h:c ELSE FONT line-orientation:0 ATTR "Name" text:(sName) line-break:words x:0.2cm y:0.2cm w:l:(2.0cm) h:c ENDIF ENDIF ENDIF
AttrRep	STRING	@INCLUDE "db:\\attrep_c_REL_CLASS_ConvLink.leo"

Name	STRING	
Representation	ENUMERATION	above/below
Rotate the visualised values by 90 degrees	ENUMERATION	No
Description	LONGSTRING	
Show name	ENUMERATION	No
Comment	STRING	
Doku	STRING	NOTEBOOK #---------- CHAPTER "Description" #---------- ATTR "Name" ATTR "Description" ATTR "Comment" ATTR "Id"